

Product Code:

7512

SPECIAL PLUS

Synthetic Blend Engine Oil

Meets the requirements:

SAE 10W-30, API SP (RC), ILSAC GF-6A, ACEA A3/B4, KIA, VW 505 00/501 01, MB 229.1, CHRYSLER MS-6395, ISUZU, TOYOTA, MAZDA, HONDA, NISSAN, SUBARU, SUZUKI, SSANGYONG, MITSUBISHI, HYUNDAI, DAEWOO

Hydro-synthetic universal motor oil for all types of gasoline engines. Designed to meet VW and DAIMLER requirements.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	870
Viscosity at 40 °C	D 445	cSt	69.2
Viscosity at 100 °C	D 445	cSt	10.79
Viscosity index	D 2270		145
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-40
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Total base no.	D 2896	mgKOH/g	10.86
Dynamic viscosity at -25 °C, max	D 5293	cP(mPas)	4396
Sulphate ash	D 874	% mass	1.1

Volume:

1L	MN7512-1	20L	MN7512-20
4L	MN7512-4	60L	MN7512-60
5L	MN7512-5	208L	MN7512-DR
7L	MN7512-7	1000L	MN7512-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®