

Product Code:

7701

ENERGY FORMULA OP

Premium Synthese Engine Oil

Meets the requirements:

SAE 5W-30, API SP, ACEA C3, ACEA C2, VW 505 01/505 00, BMW LL-04, MB 229.51, MB 229.52, MB 229.31, GM dexos2, PORSCHE C30, CHRYSLER MS-11106, FIAT 9.55535-S3, RENAULT RN17, PSA B71 2290, TOYOTA 08880-83388, TOYOTA 08880-83389, IVECO 18-1811, CLASSE SC1

Premium synthese engine oil, specially developed for gasoline and diesel engines of OPEL and GM vehicles.

- meets or exceeds the requirements of 'API SP' industry standard therefore helping address LSPI (Low Speed Pre-Ignition) and making it a preferred choice for modern direct injection turbocharged gasoline engines;

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	68.66
Viscosity at 100 °C	D 445	cSt	11.40
Viscosity index	D 2270		160
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-40
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Total base no.	D 2896	mgKOH/g	8.1
Dynamic viscosity at -30 °C, max	D 5293	cP(mPas)	5447
Sulphate ash	D 874	% mass	0.78

Volume:

1L	MN7701-1	60L	MN7701-60
4L	MN7701-4	208L	MN7701-DR
5L	MN7701-5	1000L	MN7701-IBC
20L	MN7701-20		



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®