

Product Code:

7707

ENERGY FORMULA FR

Fully Synthetic Engine Oil

Meets the requirements:

SAE 5W-30, API SP, ACEA A5/B5, FORD WSS-M2C913-D, FORD WSS-M2C913-C/-B/-A, MB 229.6, FIAT 9.55535-G1, VOLVO VCC 95200377 (Service Fill), JAGUAR STJLR.03.5003, LAND ROVER STJLR.03.5003

Innovative energy-saving ester-containing fully synthetic premium engine oil specially developed for modern diesel engines and a number of petrol engines in FORD and VOLVO vehicles, considering the requirements for heavy-duty operation and extended engine oil change intervals. The oil can be used in petrol and diesel engines of European and Asian car manufacturers requiring API SP and ACEA A5/B5 oils.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	73.68
Viscosity at 100 °C	D 445	cSt	11.96
Viscosity index	D 2270		159
Flash point COC	D 92	°C	244
Pour point	D 97	°C	-45
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Total base no.	D 2896	mgKOH/g	10.61
Dynamic viscosity at -30 °C, max	D 5293	cP(mPas)	5742
High-shear-rate viscosity at 150 °C	D 4741	cP	3.35

Volume:

1L	MN7707-1	20L	MN7707-20
5L	MN7707-5	60L	MN7707-60
7L	MN7707-7	208L	MN7707-DR
10L	MN7707-10	1000L	MN7707-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®