

Product Code:

7709

FOR TOYOTA LEXUS

Fully Synthetic Engine Oil

Meets the requirements:

SAE 5W-30, API SN Plus, ACEA A5/B5, FIAT 9.55535-G1, FORD WSS-M2C913-D/-C, FORD WSS-M2C913-A/-B, JAGUAR STJLR.03.5003, LAND ROVER STJLR.03.5003, TOYOTA 08880-80845, RENAULT RN0700, IVECO 18-1811 S1, IVECO 18-1811 S2

Universal premium synthetic engine oil specially developed for modern diesel and gasoline engines of TOYOTA and LEXUS with variable valve timing technology VVT-i, with and without a turbocharger.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	66.44
Viscosity at 100 °C	D 445	cSt	10.90
Viscosity index	D 2270		156
Flash point COC	D 92	°C	222
Pour point	D 97	°C	-42
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Total base no.	D 2896	mgKOH/g	10.45
Dynamic viscosity at -30 °C, max	D 5293	cP(mPas)	6343
Sulphate ash	D 874	% mass	0.7
High-shear-rate viscosity at 150 °C	D 4741	cP	3.48

Volume:

1L	MN7709-1	60L	MN7709-60
4L	MN7709-4	208L	MN7709-DR
20L	MN7709-20	1000L	MN7709-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®