

Product Code:

7715

LONGLIFE 504/507

Premium Synthese Engine Oil

Meets the requirements:

SAE 5W-30, API SN, ACEA C3, MB 229.51, PORSCHE C30,
BMW Longlife-04, VW TL 52 195, VW 504 00 Approval,
VW 507 00 Approval

Universal fully synthetic premium engine oil (contains PAO)
for modern petrol and diesel engines of VW group cars
(including direct injection) with and without turbocharging,
including those equipped with pump-injectors (Pumpe-
Düse).

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	71.69
Viscosity at 100 °C	D 445	cSt	11.82
Viscosity index	D 2270		161
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-45
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Total base no.	D 2896	mgKOH/g	8.75
Dynamic viscosity at -30 °C, max	D 5293	cP(mPas)	6580
High-shear-rate viscosity at 150 °C	D 4741	cP	3.60
Sulphate ash	D 874	% mass	0.7

Volume:

1L	MN7715-1	10L	MN7715-10
4L	MN7715-4	20L	MN7715-20
5L	MN7715-5	60L	MN7715-60
5L _{METAL}	MN7715-5ME	208L	MN7715-DR
7L	MN7715-7	1000L	MN7715-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®