

Product Code:

# 7722

# LONGLIFE

## 508/509

### Fully Synthetic Engine Oil

Meets the requirements:

SAE 0W-20, API SP, API SN Plus, API SP (RC),  
ACEA C6-21, ACEA C5-21, ILSAC GF-6A,  
VOLKSWAGEN 508 00, VOLKSWAGEN 509 00,  
VOLKSWAGEN TL 52 577, PORSCHE C20

Innovative energy-saving, low-viscosity, fully synthetic (PAO-based) premium engine oil for the latest models of Volkswagen turbocharged gasoline (distributed or direct injection) and diesel engines equipped with gasoline (GPFs) or diesel (DPFs) particulate filters.

#### Product Characteristics:

| Test                                | Method | Unit     | Result |
|-------------------------------------|--------|----------|--------|
| Density at 15 °C                    | D 1298 | kg/l     | 830    |
| Viscosity at 40 °C                  | D 445  | cSt      | 42.35  |
| Viscosity at 100 °C                 | D 445  | cSt      | 8.33   |
| Viscosity index                     | D 2270 |          | 177    |
| Flash point COC                     | D 92   | °C       | 224    |
| Pour point                          | D 97   | °C       | -46    |
| Ignition temperature                |        | °C       | 350    |
| Mechanical impurities               | D 2273 | %        | -      |
| Total base no.                      | D 2896 | mgKOH/g  | 10.45  |
| Dynamic viscosity at -35 °C, max    | D 5293 | cP(mPas) | 4795   |
| High-shear-rate viscosity at 150 °C | D 4741 | cP       | 2.76   |

#### Volume:

|     |           |       |            |
|-----|-----------|-------|------------|
| 1L  | MN7722-1  | 20L   | MN7722-20  |
| 5L  | MN7722-5  | 60L   | MN7722-60  |
| 10L | MN7722-10 | 208L  | MN7722-DR  |
|     |           | 1000L | MN7722-IBC |



[www.mannol.de](http://www.mannol.de)

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, [info@sct-germany.de](mailto:info@sct-germany.de), tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

# MANNOL®