

Product Code:

7726

CERAMIC PRO

Premium Synthese Engine Oil

Meets the requirements:

SAE 10W-40, API SN/CH-4, ACEA A3/B4, VW 505 00, VW 502 00, VW 501 01, VW 500 00, MB 229.3, MB 229.1, PSA B71 2296, RENAULT RN0700, RENAULT RN0710, JASO MA2

A uniquely innovative synthetic high-viscosity engine oil featuring exceptional anti-scuffing properties due to the inclusion of synthetic esters and hexagonal boron nitride h-BN (white graphite). Suitable for all types of car engines – diesel and petrol, four- and two-stroke.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	870
Viscosity at 40 °C	D 445	cSt	69.40
Viscosity at 100 °C	D 445	cSt	12.58
Viscosity index	D 2270		161
Flash point COC	D 92	°C	226
Pour point	D 97	°C	-40
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Total base no.	D 2896	mgKOH/g	10.50
Dynamic viscosity at -25 °C, max	D 5293	cP(mPas)	5220

Volume:

1L MN7726-1

4L MN7726-4

5L MN7726-5



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®