

Product Code:

7727

CERAMIC ULTRA

Premium Synthese Engine Oil

Meets the requirements:

SAE 5W-40, ACEA A3/B4, MB 229.5, MB 229.3, MB 226.5, JASO MA2, VOLKSWAGEN 502 00, VOLKSWAGEN 505 00, PORSCHE A40, RENAULT RN0710, RENAULT RN0700, API SN/CH-4, BMW LL-01, BMW LL-98, PSA B71 2296, FIAT 9.55535-H2, FIAT 9.55535-Z2, CHRYSLER MS-10850, CHRYSLER MS-10896, CHRYSLER MS-12991, GM LL-A-025, GM LL-B-025

Unique innovative synthetic high-viscosity premium-class engine oil with special anti-scutting properties thanks to the addition of synthetic esters and hexagonal boron nitride h-BN (white graphite). Suitable for all types of car engines – diesel and petrol, four- and two-stroke.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	77.50
Viscosity at 100 °C	D 445	cSt	12.54
Viscosity index	D 2270		160
Flash point COC	D 92	°C	230
Pour point	D 97	°C	-40
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Total base no.	D 2896	mgKOH/g	10.53
Dynamic viscosity at -30 °C, max	D 5293	cP(mPas)	6020

Volume:

1L	MN7727-1
4L	MN7727-4
5L	MN7727-5



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®