

Product Code:

7730

LEGEND 504/507

Longlife Engine Oil

Meets the requirements:

SAE 0W-30, ACEA C3, MB 229.52, MB 229.31,
MB 229.51, VOLKSWAGEN TL 52545, BMW Longlife-04,
PORSCHE C30, VOLKSWAGEN 504 00 Approval,
VOLKSWAGEN 507 00 Approval

Innovative energy-saving bi-synthetic (PAO + ester) premium engine oil with improved low-temperature properties for modern gasoline and diesel engines (including those with direct injection) with and without turbocharging, including those equipped with pump-injectors (Pumpe-Düse). Developed based on the requirements of VW and DAIMLER.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	55.78
Viscosity at 100 °C	D 445	cSt	10.42
Viscosity index	D 2270		179
Flash point COC	D 92	°C	240
Pour point	D 97	°C	-51
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Total base no.	D 2896	mgKOH/g	8.82
Dynamic viscosity at -35 °C, max	D 5293	cP(mPas)	5772
High-shear-rate viscosity at 150 °C	D 4741	cP	3.52
Sulphate ash	D 874	% mass	0.7

Volume:

1L	MN7730-1	60L	MN7730-60
5L	MN7730-5	208L	MN7730-DR
20L	MN7730-20	1000L	MN7730-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®