Product Code:

7808

V-TWIN 4-TAKT

Fully Synthetic 4-stroke Engine Oil



Meets the requirements:

SAE 20W-50, API SG, SL, SM, CF, CG-4, CJ-4, JASO MA/MA2, ISO L-EMA2, HARLEY-DAVIDSON, BMW CRUISER, INDIAN, VICTORY MOTORCYCLES, YAMAHA MOTORCYCLES, KAWASAKI, ROYAL ENFIELD, TRIUMPH MOTORCYCLES, HONDA, SUZUKI

Universal fully synthetic engine oil for normally and highly loaded four-stroke engines of road, off-road, and racing motorcycles with V-Twin engines operating at high temperatures, such as Harley Davidson, as well as in conditions where gear surfaces are subjected to maximum pressure and corrosion caused by short ride and storage. Designed to ensure guaranteed engine protection and provide long-lasting transmission and chain durability. Contains esters.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	870
Viscosity at 40 °C	D 445	cSt	144.30
Viscosity at 100 °C	D 445	cSt	19.31
Viscosity index	D 2270		152
Flash point COC	D 92	°C	226
Pour point	D 97	°C	-43
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Total base no.	D 2896	mgKOH/g	1.44
Dynamic viscosity at -15 °C, max	D 5293	°C	3093

Volume:

1L	MN7808-1
4L	MN7808-4

www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®