

Product Code:

7830

4-TAKT HD MOTORBIKE

Universal 4-stroke Engine Oil

Meets the requirements:

SAE 20W-50, API SN, JASO MA/MA2

A universal all-season synthetic-based engine oil for 4-stroke normal- and high-load engines (including 2-cylinder V-type) for highway, off-road and racing motorcycles. It was designed for a guaranteed protection of the engine and the durability of the gearbox.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	890
Viscosity at 40 °C	D 445	cSt	154.5
Viscosity at 100 °C	D 445	cSt	17.17
Viscosity index	D 2270		120
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-34
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Total base no.	D 2896	mgKOH/g	7.46
Dynamic viscosity at -15 °C, max	D 5293	cP(mPas)	9346
High-shear-rate viscosity at 150 °C	D 4741	cP	3.92
Sulphate ash	D 874	% mass	0.89

Volume:

1L	MN7830-1	60L	MN7830-60
10L	MN7830-10	208L	MN7830-DR
20L	MN7830-20	1000L	MN7830-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®