

Product Code:

7902

RACING +ESTER

Premium Synthese Engine Oil

Meets the requirements:

SAE 10W-60, API SN/CH-4, ACEA A3/B4, VW 501 01
VW 505 00, MB 229.1, FIAT 9.55535-H3, PSA B71 2300

Universal bi-synthetic (PAO + esters) premium motor oil designed for new generations of all types of engines operating in harsh and extreme operating conditions. Designed to meet the requirements of manufacturers of sports and racing cars.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	870
Viscosity at 40 °C	D 445	cSt	158.8
Viscosity at 100 °C	D 445	cSt	22.57
Viscosity index	D 2270		170
Flash point COC	D 92	°C	226
Pour point	D 97	°C	-45
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Total base no.	D 2896	mgKOH/g	10.71
Dynamic viscosity at -25 °C, max	D 5293	cP(mPas)	5431
High-shear-rate viscosity at 150 °C	D 4741	cP	3.88
Sulphate ash	D 874	% mass	1.13

Volume:

1L	MN7902-1	60L	MN7902-60
4L	MN7902-4	208L	MN7902-DR
10L	MN7902-10	1000L	MN7902-IBC
20L	MN7902-20		



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®