

Product Code:

7903

ELITE

Fully Synthetic Engine Oil

Meets the requirements:

SAE 5W-40, ACEA A3/B4, API SP, MB 229.5, MB 229.3, MB 226.5, JASO MA2, VW 502 00, VW 505 00, PORSCHE A40, RENAULT RN0710, RENAULT RN0700, BMW LL-01, BMW LL-98, PSA B71 2296, FIAT 9.55535-H2, FIAT 9.55535-Z2, CHRYSLER MS-10850, CHRYSLER MS-10896, CHRYSLER MS-12991, GM LL-A-025, GM LL-B-025

Innovative universal ester-containing premium motor oil for modern gasoline and diesel engines with and without turbocharging, including "old" brands and high mileage. Designed based on the requirements of European producers.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	86.54
Viscosity at 100 °C	D 445	cSt	13.64
Viscosity index	D 2270		160
Flash point COC	D 92	°C	234
Pour point	D 97	°C	-42
High-shear-rate viscosity at 150 °C	D 4741	cP	3.64
Dynamic viscosity at -30 °C	D 5293	cP(mPas)	6405
Total base no.	D 2896	mgKOH/g	10.65
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-

Volume:

1L	MN7903-1	20L	MN7903-20
4L	MN7903-4	60L	MN7903-60
5L	MN7903-5	208L	MN7903-DR
10L	MN7903-10	1000L	MN7903-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®