

Product Code:

7904

DIESEL TURBO

Fully Synthetic Engine Oil

Meets the requirements:

SAE 5W-40, API CI-4/SN, ACEA A3/B4, JASO MA2
MB 229.3, MB 226.5/229.5, VW502 00/505 00
PORSCHE A40, RENAULT RN0700/RN0710
BMW LL-01/-98, PSA B71 2294, PSA B71 2296
FIAT 9.55535-M2, FIAT 9.55535-N2/-H2/-Z2
CHRYSLER MS-10725/MS-10850/MS-10896/MS-12991
GM LL-A-025, GM LL-B-025

Innovative ester-containing fully synthetic premium engine oil for modern high-performance turbo diesel engines. Developed in accordance with the requirements of the VW group.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	83
Viscosity at 100 °C	D 445	cSt	13,44
Viscosity index	D 2270		165
Flash point COC	D 92	°C	236
Pour point	D 97	°C	-40
TBN	D 2896	mgKOH/g	10,65
Ignition temperature		°C	350
Mechanical impurities	D 2273	°C	-
Dynamic viscosity at -30 °C max	D 5293	[cP](mPas)	5927

Volume:

1L	MN7904-1	20L	MN7904-20
5L	MN7904-5	60L	MN7904-60
10L	MN7904-10	208L	MN7904-DR



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®