

Product Code:

7906

ENERGY ULTRA JP

Synthetic Engine Oil

Meets the requirements:

SAE 5W-20, API SP (RC), ILSAC GF-6A, ACEA C5,
FORD WSS-M2C948-A, FORD WSS-M2C948-B

Innovative energy-saving premium bi-synthetic engine oil (PAO + esters) for modern gasoline and diesel engines. Designed to meet the requirements of American, Japanese and Korean automakers.

- For turbocharged engines with direct injection, a unique oil formulation reduces to zero the effect of premature ignition of the fuel mixture LSPI (LowSpeed Pre-Ignition);

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	830
Viscosity at 40 °C	D 445	cSt	42.30
Viscosity at 100 °C	D 445	cSt	7.96
Viscosity index	D 2270		163
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-45
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Total base no.	D 2896	mgKOH/g	8.02
Dynamic viscosity at -30 °C, max	D 5293	cP(mPas)	6100
High-shear-rate viscosity at 150 °C, min	D 4741	cP	3.12

Volume:

1L	MN7906-1	60L	MN7906-60
4L	MN7906-4	208L	MN7906-DR
5L	MN7906-5	1000L	MN7906-IBC
20L	MN7906-20		



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®