

Product Code:

7907

ENERGY COMBI LL

Longlife Engine Oil

Meets the requirements:

SAE 5W-30, API SN, ACEA C3, BMW LL-04,
VW TL 52 195, MB Approval 229.51 Approval,
VW 504 00 Approval, VW 507 00 Approval,
PORSCHE C30

Innovative universal multigrade bi-synthetic (PAO) premium motor oil for modern gasoline and diesel engines (including those with direct injection) with and without turbocharging, including those equipped with pump nozzles (Pumpe-Duse). Designed based on VW and DAIMLER requirements.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	70.77
Viscosity at 100 °C	D 445	cSt	12.24
Viscosity index	D 2270		172
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-48
Total base no.	D 2896	mgKOH/g	8.99
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Dynamic viscosity at -30 °C, max	D 5293	cP(mPas)	6174
High-shear-rate viscosity 150 °C	D 4741	cP	3.54

Volume:

1L	MN7907-1	20L	MN7907-20
4L	MN7907-4	60L	MN7907-60
5L	MN7907-5	208L	MN7907-DR
10L	MN7907-10	1000L	MN7907-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®