

Product Code:

7908

ENERGY PREMIUM

Fully Synthetic Engine Oil

Meets the requirements:

SAE 5W-30, API SP (RC), ILSAC GF-6A, ACEA C2-23, ACEA C3-23, MB 229.51, MB 229.31, BMW LL-04, OPEL OV0401547 G30 & D30, FORD WSS-M2C961-A1, API SQ, FIAT 9.55535-S1, MB - Approval 229.52

Innovative, versatile, all-synthetic ester-containing premium synthetic engine oil for modern diesel and gas turbocharged and non-turbocharged engines. Designed in accordance with the requirements of European automakers.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	70.71
Viscosity at 100 °C	D 445	cSt	11.67
Viscosity index	D 2270		160
Flash point COC	D 92	°C	224
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Total base no.	D 2896	mgKOH/g	8.55
Dynamic viscosity at -30 °C, max	D 5293	cP(mPas)	6550
Pour point	D 97	°C	-42

Volume:

1L	MN7908-1	20L	MN7908-20
4L	MN7908-4	60L	MN7908-60
5L	MN7908-5	208L	MN7908-DR
7L	MN7908-7	1000L	MN7908-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®