

Product Code:

7909

DIESEL TDI

Synthetic Engine Oil

Meets the requirements:

SAE 5W-30, API SN/CH-4, ACEA C2, ACEA C3,
VOLKSWAGEN 505 01, BMW LL-04, MB 229.51,
MB 229.52, MB 229.31, MB 226.5, GM dexos2,
RENAULT RN0700, RENAULT RN0710

Innovative universal ester-containing fully synthetic premium motor oil for modern diesel and gasoline engines with and without turbocharging. Especially recommended for direct injection turbodiesel engines. Designed to meet VW requirements.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	73.84
Viscosity at 100 °C	D 445	cSt	12.29
Viscosity index	D 2270		165
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-42
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Total base no.	D 2896	mgKOH/g	8.35
Dynamic viscosity at -30 °C, max	D 5293	cP(mPas)	6171
High-shear-rate viscosity at 150 °C	D 4741	cP	3.52
Sulphate ash, max	D 874	% mass	0.72

Volume:

1L	MN7909-1	20L	MN7909-20
5L	MN7909-5	60L	MN7909-60
10L	MN7909-10	208L	MN7909-DR
		1000L	MN7909-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®