

Product Code:

7913

ENERGY FORMULA PD

HC Synthese Engine Oil

Meets the requirements:

SAE 5W-40, API SN, ACEA C3, MB 229.51/229.31/226.5, GM dexos2, PORSCHE A40, VW 505 00/505 01, ACEA C2, FORD WSS-M2C917-A, BMW LL-04, FIAT 9.55535-S2, FIAT 9.55535-GH2, RENAULT RN0700, RENAULT RN0710, CHRYSLER MS-1106

Innovative universal energy-saving ester-containing fully synthetic premium motor oil for modern diesel engines (including those with direct injection) and gasoline engines with and without turbocharging, including those equipped with pump nozzles (Pumpe-Duse). Designed based on VW and DAIMLER requirements.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	80.20
Viscosity at 100 °C	D 445	cSt	13.39
Viscosity index	D 2270		170
Flash point COC	D 92	°C	226
Pour point	D 97	°C	-42
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Total base no.	D 2896	mgKOH/g	8.13
Dynamic viscosity at -30 °C, max	D 5293	cP(mPas)	5749
Sulphate ash	D 874	% mass	0.79

Volume:

1L	MN7913-1	60L	MN7913-60
5L	MN7913-5	208L	MN7913-DR
10L	MN7913-10	1000L	MN7913-IBC
20L	MN7913-20		



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®