

Product Code:

7915

EXTREME

Synthese Engine Oil

Meets the requirements:

SAE 5W-40, ACEA A3/B4, MB 229.5/229.3, MB 226.5, JASO MA2, VW 502 00/505 00, PORSCHE A40, RENAULT RN0710/0700, API SP, BMW LL-01/-98, PSA B71 2296, FIAT 9.55535-H2/-Z2, GM LL-A-025, GM LL-B-025, CHRYSLER MS-10850/-10896, CHRYSLER MS-12991

Innovative universal ester-containing premium motor oil for modern gasoline and diesel engines with and without turbocharging, including "old" brands and high mileage. Designed based on the requirements of European producers.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	80.59
Viscosity at 100 °C	D 445	cSt	13.30
Viscosity index	D 2270		168
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-38
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Total base no.	D 2896	mgKOH/g	10.26
Dynamic viscosity at -30 °C, max	D 5293	cP(mPas)	5482
High-shear-rate viscosity 150 °C, min	D 4741	cP	3.70

Volume:

1L	MN7915-1	20L	MN7915-20
4L	MN7915-4	60L	MN7915-60
5L	MN7915-5	208L	MN7915-DR
10L	MN7915-10	1000L	MN7915-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®