

Product Code:

7917

ENERGY FORMULA C4

Synthetic Engine Oil

Innovative universal ester-containing fully synthetic premium engine oil for modern diesel and gasoline engines with and without turbocharger equipped with particulate filters (DFP / FAP). The product is specifically designed for professional Renault car maintenance.

Meets the requirements:

SAE 5W-30, ACEA C4, API SN

RENAULT RN0720

MB 226.51/229.51/229.31

NISSAN Diesel engines with DPF

Product Characteristics:

Parameter name	Test method	Standard	Results
Viscosity at 100°C, cSt	ASTM D-445	11-12,5	12,14
Viscosity at 40°C, cSt	ASTM D-445	-	68,84
Dynamic viscosity [cP](mPas), at -30°C, max	ASTM D-5293	6600	4910
Viscosity index, min	ASTM D-2270	150	175
High-shear-rate viscosity, cP at 150°C, min	ASTM D-4741	3,5	3,54
Flash point, open cup, °C	ASTM D-92	220	224
Pour point, °C, max	ASTM D-97	-35	-45
Total base no. mgKOH/g, min	ASTM D-2896	7,70	8,05
Density at 15°C, kg/l, max	ASTM D-1298	0,9	0,85
Ignition temperature, °C not below		>250	350

Volume:

1L	MN7917-1	60L	MN7917-60
5L	MN7917-5	208L	MN7917-DR
10L	MN7917-10	1000L	MN7917-IBC
20L	MN7917-20		



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®