

Product Code:

7918

LEGEND ULTRA

Fully Synthetic Engine Oil

Meets the requirements:

SAE 0W-20, API SP (RC), ILSAC GF-6A, HONDA HTO-06, GM dexos 1 Gen3, GM 6094M, CHRYSLER MS-6395, CHRYSLER MS-13340, JAGUAR STJLR.51.5122, INFINITI, LAND ROVER STJLR.51.5122, FORD WSS-M2C947-A, FORD WSS-M2C947-B1, LEXUS, MAZDA, SUZUKI

Innovative energy-saving premium bi-synthetic engine oil (PAO + esters) for modern gasoline engines. Designed to meet the requirements of American, Japanese and Korean automakers.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	830
Viscosity at 40 °C	D 445	cSt	44.30
Viscosity at 100 °C	D 445	cSt	8.32
Viscosity index	D 2270		166
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-45
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Total base no.	D 2896	mgKOH/g	8.31
Dynamic viscosity at -35 °C, max	D 5293	cP(mPas)	5584

Volume:

1L	MN7918-1	20L	MN7918-20
4L	MN7918-4	60L	MN7918-60
5L	MN7918-5	208L	MN7918-DR
10L	MN7918-10	1000L	MN7918-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®