

Product Code:

7919

LEGEND EXTRA

Premium PAO-Based Engine Oil

Meets the requirements:

SAE 0W-30, API SQ/Resource Conserving, API SP (RC),
API SN Plus (RC) ACEA C2, ACEA C3, BMW LL-12FE,
MB 229.61, FIAT 9.55535-DS-1, FORD WSS-M2C950-A,
OPEL OV0401547, PSA B71 2290, PSA B71 2312,
ILSAC GF-7A, GM Dexos1 Gen 3, GM 4718M, FORD,
GMC, CADILLAC, CHEVROLET, GENESIS, HYUNDAI,
KIA, MAZDA, MITSUBISHI, TOYOTA, BUICK

Innovative universal bi-synthetic (PAO+esters) premium
engine oil for modern petrol and diesel engines with and
without turbocharging.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	68.78
Viscosity at 100 °C	D 445	cSt	12.23
Viscosity index	D 2270		177
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-45
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Total base no.	D 2896	mgKOH/g	8.55
Dynamic viscosity at -35 °C, max	D 5293	cP(mPas)	6150
High-shear-rate viscosity at 150 °C	D 4741	cP	3.52

Volume:

1L	MN7919-1	20L	MN7919-20
4L	MN7919-4	60L	MN7919-60
5L	MN7919-5	208L	MN7919-DR
10L	MN7919-10	1000L	MN7919-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®