

Product Code:

7920

HYBRID SQ

Advanced Fuel Saving Engine Oil

Meets the requirements:

SAE 0W-16, API SQ (RC), ILSAC GF-7B, HONDA Ultra Green, HONDA 08215-99974, HONDA 08216-99974, HONDA 08232-P99S1LHE, MITSUBISHI MZ102661, MITSUBISHI MZ102662, MITSUBISHI DiaQueen ECO Plus, NISSAN KLANM-01A04 Extra Save X Eco, TOYOTA 08880-11005

Innovative energy-saving low-viscosity engine oil of the latest generation on a bi-synthetic (PAO + esters) basis for modern gasoline engines. Designed in accordance with the latest API SQ and ILSAC GF-7B standards, it is especially recommended for hybrid cars, but it is also suitable for non-hybrid, requiring oils of such viscosity and with similar performance properties.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	840
Viscosity at 40 °C	D 445	cSt	43.35
Viscosity at 100 °C	D 445	cSt	8.20
Viscosity index	D 2270		167
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-47
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Total base no.	D 2896	mgKOH/g	9.25
Dynamic viscosity at -35 °C, max	D 5293	cP(mPas)	5999
High-shear-rate viscosity at 150 °C	D 4741	cP	2.25

Volume:

1L	MN7920-1	60L	MN7920-60
5L	MN7920-5	208L	MN7920-DR
20L	MN7920-20	1000L	MN7920-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®