

Product Code:

7921

LEGEND FORMULA C5

Fully Synthetic Engine Oil

Meets the requirements:

SAE 0W-20, ACEA C5, API SP (RC), BMW LL-17FE+, VOLVO VCC RBS0-2AE (ServiceFill), OPEL Ov0401547, GM dexos 1 Gen3, HONDA HTO-06, GM Dexos D, GM 6094M, CHRYSLER MS-6395, CHRYSLER MS-13340, JAGUAR STJLR.51.5122, LAND ROVER STJLR.51.5122, JAGUAR STJLR.03.5006, FORD WSS-M2C947-A, LAND ROVER STJLR.03.5006, FORD WSS-M2C947-B1, MB - Approval 229.71, MB - Approval 229.72

Innovative energy-saving, low-viscosity bi-synthetic (PAO + esters) premium engine oil for the latest models of turbocharged gasoline engines (multipoint or direct injection) with gasoline particulate filters.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	830
Viscosity at 40 °C	D 445	cSt	45.20
Viscosity at 100 °C	D 445	cSt	8.37
Viscosity index	D 2270		164
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-45
Total base no.	D 2896	mgKOH/g	8.44
Dynamic viscosity at -35 °C, max	D 5293	cP(mPas)	6180
High-shear-rate at 150 °C, min	D 4741	cP	2.64
Sulphate ash	D 874	% mass	0.75

Volume:

1L	MN7921-1	20L	MN7921-20
5L	MN7921-5	60L	MN7921-60
10L	MN7921-10	208L	MN7921-DR
		1000L	MN7921-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®