

Product Code:

7925

FOR

CHINESE CARS

Fully Synthetic Engine Oil

Engine Oil is formulated with fully synthetic base oils and high-quality multifunctional additives. It provides excellent oxidation resistance, deposit and wear protection, and can help achieve better fuel economy.

Meets the requirements:

SAE 5W-20, API SP, SN (RC), ILSAC GF-6A, CHANGAN, GM Dexos 1 Gen3, CHRYSLER MS6395, SAIC, CHERY, FORD WSS-M2C961-A1, FORD WSS-M2C946B1, GEELY, BYD, JETOUR, GAC, Haval

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 4052	kg/l	0.847
Viscosity at 40 °C	D 445	mm ² /s	46.18
Viscosity at 100 °C	D 445	mm ² /s	8.35
Viscosity index	D 2270		162
Flash point COC	D 92	°C	224
Low Temperature Pumpability (MRV) at -35 °C	D 4684	mPas	15 900
Pour point	D 4684	°C	-39

Volume:

1L	MN7925-1
5L	MN7925-5
200L	MN7925-DR



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®