

Product Code:

7928

FOR CHINESE CARS

Fully Synthetic Engine Oil

Meets the requirements:

SAE 0W-20, API SP, ILSAC GF-6A, GM Dexos 1 Gen3, CHRYSLER Ms6395, FORD WSS-M2C961-A1, FORD WSS-M2C946-B1, SAIC, Geely, BYD, GAC, Changan, Haval, Chery, Jetour, Wuling, Hongqi, GREAT WALL

Fully synthetic low-viscosity engine oil for modern petrol engines of passenger cars with direct and multi point fuel injection, turbocharged (TGDI/GDI/TFSI) and non-turbocharged, equipped with variable valve timing (VVT), dual injection and start-stop system. Developed in accordance with the requirements of Chinese car manufacturers. Contains esters.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	840
Viscosity at 40 °C	D 445	cSt	46.11
Viscosity at 100 °C	D 445	cSt	8.59
Viscosity index	D 2270		167
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-45
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Total base no.	D 2896	mgKOH/g	8.06
Dynamic viscosity at -35 °C, max	D 5293	cP(mPas)	5797

Volume:

1L	MN7928-1	20L	MN7928-20
4L	MN7928-4	60L	MN7928-60
5L	MN7928-20	208L	MN7928-DR
		1000L	MN7928-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®