

Product Code:

7929

GLV-ONE

Premium Synthese Engine Oil

Meets the requirements:

SAE 0W-8, API SP, API SQ, JASO GLV-1

Innovative energy-saving fully synthetic motor oil of the latest generation with ultra-low viscosity based on polyalphaolefins (PAO). Contains a complex of organic friction modifiers and synthetic esters. Designed for modern passenger gasoline and diesel engines with and without turbocharging and with direct fuel injection. Especially recommended for hybrid engines. Developed in accordance with the latest API SQ and JASO GLV-1 standards.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	29.67
Viscosity at 100 °C	D 445	cSt	5.93
Viscosity index	D 2270		149
Flash point COC	D 92	°C	230
Pour point	D 97	°C	-42
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Total base no.	D 2896	mgKOH/g	7.60
Dynamic viscosity at -35 °C, max	D 5293	cP(mPas)	4262
High-shear-rate viscosity at 150 °C	D 4741	cP	1.78

Volume:

5L	MN7929-5
20L	MN7929-20
208L	MN7929-DR



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®