

Product Code:

8102

MAXPOWER 4x4

Premium Synthetic Gear Oil

Meets the requirements:

SAE 75W-140, API GL-5 LS (Limited Slip), MIL L 2105 D,
MAN 342, SCANIA STO 1:0

All-season last-generation gear oil (contains PAO) specially designed for the lubrication of all types of differentials, including excessive friction differentials where the oil "Limited Slip Oil API GL5" is required. It was developed for hypoid, bevel and spiral gears.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	890
Viscosity at 40 °C	D 445	cSt	231.1
Viscosity at 100 °C	D 445	cSt	24.72
Viscosity index	D 2270		135
Flash point COC	D 92	°C	216
Pour point	D 97	°C	-42
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-

Volume:

1L	MN8102-1	208L	MN8102-DR
20L	MN8102-20	1000L	MN8102-IBC
60L	MN8102-60		



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®