

Product Code:

8105

HYPROID LSD

Universal Gear Oil

Meets the requirements:

SAE 85W-140, API GL-5 LS (Limited Slip), MIL L 2105 D

A universal all-season high-viscosity mineral-based gear oil for manual transmissions. It was developed for a safe and reliable operation of self-locking differentials (differentials with excessive friction/limited slip - LS), main gears with hypoid pinions and other manual transmission parts with bevel, worm and cylindrical pairs withstanding extreme (including impact) loads and high operating temperatures.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	890
Viscosity at 40 °C	D 445	cSt	350.0
Viscosity at 100 °C	D 445	cSt	26.39
Viscosity index	D 2270		100
Flash point COC	D 92	°C	228
Pour point	D 97	°C	-18
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-

Volume:

4L	MN8105-4	60L	MN8105-60
10L	MN8105-10	208L	MN8105-DR
20L	MN8105-20	1000L	MN8105-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®