

Product Code:

8107

UNIVERSAL GEAR OIL

Universal Gear Oil

Meets the requirements:

SAE 80W-90, API GL-4, MIL L 2105

A universal all-season mineral-based gear oil. It was developed for all types of synchronized and non-synchronized manual transmissions, drive axles and other components of manual transmissions operating under sustainable and heavy loads.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	900
Viscosity at 40 °C	D 445	cSt	143.18
Viscosity at 100 °C	D 445	cSt	15.14
Viscosity index	D 2270		107
Flash point COC	D 92	°C	216
Pour point	D 97	°C	-32
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Brookfield dynamic viscosity at -26 °C	D 2983	cP(mPas)	144 000

Volume:

1L	MN8107-1		
4L	MN8107-4	60L	MN8107-60
10L	MN8107-10	208L	MN8107-DR
20L	MN8107-20	1000L	MN8107-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®