

Product Code:

8108

BASIC PLUS

Fully Synthetic Gear Oil

Meets the requirements:

SAE 75W-90, API GL 4+, MIL L 2105,
VOLKSWAGEN 501 50

An all-season universal last-generation energy-conserving gear oil (containing PAO) designed specially for the lubrication of manual transmissions with an incorporated differential of front drive vehicles. It is suitable for all types of synchronized and non-synchronized manual transmissions (including heavy-loaded). It was developed on the basis of the requirements set by the VW Group.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	890
Viscosity at 40 °C	D 445	cSt	81.76
Viscosity at 100 °C	D 445	cSt	14.02
Viscosity index	D 2270		177
Flash point COC	D 92	°C	216
Pour point	D 97	°C	-43
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Brookfield dynamic viscosity at -40 °C	D 2983	cP(mPas)	148 000

Volume:

1L	MN8108-1	60L	MN8108-60
4L	MN8108-4	208L	MN8108-DR
20L	MN8108-20		



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®