

Product Code:

8109

UNIGEAR

Synthetic Gear Oil

Meets the requirements:

SAE 75W-80, API GL-4/GL-5 LS, MIL L 2105 C,
FORD WSD-M2C200-C, MACK GO-J Plus,
PSA B71 2330

A universal energy-conserving synthetic gear oil. It may be used in all manual transmission devices, including 5- and 6-speed synchronized manual transmissions, transmissions with an incorporated differential of front wheel drive vehicles, transfer cases and main gears, including hypoid.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/m³	850
Viscosity at 40 °C	D 445	CSt	42,99
Viscosity at 100 °C	D 445	CSt	8,68
Viscosity index	D 2270		186
Pour point, max	D 97	°C	-46
Flash point	D 92	°C	216
Brookfield dynamic viscosity at -40 °C	D 2983	°C	130 500

Volume:

1L	MN8109-1	60L	MN8109-60
20L	MN8109-20	208L	MN8109-DR



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®