

Product Code:

8111

TG-1 UNIVERSAL

Industrial Hydraulic Oil

Meets the requirements:

SAE 75W-80, API GL-4, EATON Manual Transmission,
MAN 341 Type Z4, MAN 341 Type E3, VOLVO 97307,
ZF TE-ML 01L, ZF TE-ML 02L, ZF TE-ML 16K

A latest-generation universal energy-conserving completely synthetic all-season gear oil in compliance with the newest world standards. It is suitable for all synchronized and non-synchronized manual transmission types operating under heavy loads and at high speed in extremely low temperatures. It is developed on the basis of the requirements of European and American truck manufacturers.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/m³	850
Viscosity at 40 °C	D 445	CSt	41,99
Viscosity at 100 °C	D 445	CSt	8,59
Viscosity index	D 2270		216
Pour point, max	D 97	°C	-50
Flash point	D 92	°C	216
Brookfield dynamic viscosity at -40 °C	D 2983	°C	130 500

Volume:

10L	MN8111-10	208L	MN8111-DR
20L	MN8111-20	1000L	MN8111-IBC
60L	MN8111-60		



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®