

Product Code:

8112

TG-2 HYPOID

Synthetic Gear & Axle Oil

Meets the requirements:

SAE 75W-90, SAE J2360, API GL-4/GL-5, API MT-1,
MAN 341 Z2, MIL L 2105 D/PRF 2105 E, EATON Europe,
MAN 341 S1, MB 235.8, MERITOR O-76-N, SCANIA STO 1:0,
VOLVO 97312, ZF TE-ML 02B, ZF TE-ML 05A, ZF TE-ML 12L,
ZF TE-ML 12N, ZF TE-ML 16F, ZF TE-ML 17B, ZF TE-ML 19C,
ZF TE-ML 21A

A latest-generation universal energy-conserving completely synthetic all-season gear oil in compliance with the newest world standards. It is suitable for all types of synchronized and non-synchronized manual transmissions (especially heavy-load), transfer cases and main gears with hypoid gears. It is developed on the basis of the requirements of European and American truck manufacturers.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	890
Viscosity at 40 °C	D 445	cSt	80.85
Viscosity at 100 °C	D 445	cSt	13.95
Viscosity index	D 2270		179
Flash point COC	D 92	°C	216
Pour point	D 97	°C	-45
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Brookfield dynamic viscosity at -40 °C	D 2983	cP(mPas)	150 000

Volume:

5L	MN8112-5	60L	MN8112-60
10L	MN8112-10	208L	MN8112-DR
20L	MN8112-20	1000L	MN8112-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®