

Product Code:

8115

MTF-3

Fully Synthetic Transmission Fluid

Meets the requirements:

SAE 75W, API GL-4, TOYOTA LV, NISSAN LV MTF-1, MB 235.71, VW G 052 798/G 052 727/G 052 749, VW TL 521 71 (G 052 171 A1)/TL 521 71 (G 052 171 A2), VW TL 521 78 (G 052 178 A2)/TL 525 12 (G 052 512 A2), VW TL 726 (G 052 726 A2)/TL 726 (G 055 726 A2), VW TL 726 (G 060 726 A2)/TL 726 (G 070 726 A2), BMW 83 220 396 706/83 22 7 533 818/2300 7533 818, BMW MTF LT-3/MTF LT-2, FORD WSS-M2C200-D2, PSA 9730 A8, TOYOTA 08885-81081, VOLVO 1161838, VOLVO 1161839, Others JWS 2271

Universal energy-saving all-season transmission fully synthetic oil of the latest generation specially developed for use in robotic and manual gearboxes of TOYOTA and FORD cars (Attention! Not for all manual transmissions). Applicable for transfer cases and differentials. Developed based on the requirements of the TOYOTA group.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/m³	850
Viscosity at 40 °C	D 445	CSt	45,22
Viscosity at 100 °C	D 445	CSt	8,26
Viscosity index	D 2270		160
Pour point, max	D 97	°C	-46
Flash point	D 92	°C	216
Brookfield dynamic viscosity at -40 °C	D 2983	°C	145 000

Volume:

1L	MN8115-1	208L	MN8115-DR
20L	MN8115-20	1000L	MN8115-IBC
60L	MN8115-60		



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®