

Product Code:

8205

DEXRON II

Automatic transmission fluid

Meets the requirements:

ALLISON C4, CATERPILLAR TO-2, GM Dexron II D, MAN 339 V1/Z1, MB 236.5/236.7, RENK, VOITH H 55.6335.xx (G607), ZF TE-ML 03D/04D, ZF TE-ML 11A/14A/17C

A universal all-season mineral-based transmission fluid (ATF) for automatic gearboxes, hydraulic power steering systems, cab tilt mechanisms, car hydraulic clutches and other hydraulic devices, including the ones operating under heavy-duty conditions in trucks and off-road vehicles. It ensures a flawless operation of an automatic gearbox, guarantees minimal wear, a lasting service life of transmissions and fuel economy. It was developed on the basis of the requirements set by the GM group.

Product Characteristics:

Test	Method	Unit	Result
Color			RED
Density at 15 °C	D 1298	kg/m³	850
Viscosity at 40 °C	D 445	CSt	40,54
Viscosity at 100 °C	D 445	CSt	6,94
Viscosity index	D 2270		131
Flash point COC	D 92	°C	216
Pour point	D 97	°C	-46
Brookfield dynamic viscosity at -40 °C	D 2983	cP(mPas)	45 000

Volume:

1L	MN8205-1	60L	MN8205-60
4L	MN8205-4	208L	MN8205-DR
10L	MN8205-10	1000L	MN8205-IBC
20L	MN8205-20		



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®