

Product Code:

8206

DEXRON III

Automatic Transmission Fluid

Meets the requirements:

ALLISON C4, CATERPILLAR TO-2, FORD Mercon V, FORD ESP-M2C138-CJ, FORD ESP-M2C166-H, GM Dexron III H, GM Dexron III G, GM Dexron III F, MB 236.1, VOITH H 55.6335.xx (G607), ZF TE-ML 09, ZF TE-ML 11, ZF TE-ML 14

A universal all-season synthetic-based transmission fluid (ATF) for automatic gearboxes, hydraulic converters, hydraulic power steering systems, car hydraulic clutches and other hydraulic devices, including the ones operating under heavy-duty conditions in trucks and off-road vehicles. It ensures a flawless operation of an automatic gearbox, guarantees minimal wear, a lasting service life of transmissions and fuel economy. It was developed on the basis of the requirements set by GM and Ford groups.

Product Characteristics:

Test	Method	Unit	Result
Color			RED
Density at 15 °C	D 1298	kg/m ³	850
Viscosity at 40 °C	D 445	CSt	33,97
Viscosity at 100 °C	D 445	CSt	7,21
Viscosity index	D 2270		184
Flash point COC	D 92	°C	216
Pour point	D 97	°C	-46
Brookfield dynamic viscosity at -40 °C	D 2983	cP(mPas)	18 000

Volume:

1L	MN8206-1	60L	MN8206-60
4L	MN8206-4	208L	MN8206-DR
10L	MN8206-10	1000L	MN8206-IBC
20L	MN8206-20		



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®