

Product Code:

8207

DEXRON VI

Automatic Transmission Fluid

Meets the requirements:

JASO M315, Class 1-A-LV, AISIN WARNER JWS 3309/3324, AISIN WARNER ATF-0T4/ATF-0WS, CITROEN Z 000169756ALLISON C3/C2/C4, BENTLEY PY112995PA, BOSCH TE-ML 09, GM AW-1, FORD ESP-M2C138-CJ-M2C166-H, FORD XT-10-QLV [LV], FORD XT-2-QDX [M]/-2-QSM [Syn], FORD XT-5-QM [V]/-5-QSM [V Syn], FORD XT-6-QSP [SP], FORD XT-8-QAW [Premium], FORD XT-9- QMM5 [FRN5], FORD WSS-M2C922-A1, FORD Mercon LV, GM Type A Suffix A, GM Saturn T-IV Fluid, GM Saturn 22689186, GM ATF Z1, GM Saturn 22717466, GM 19256039, GM Dex-VI [GMW 16444], GM Dex [GM 6032M], GM Dex-B [GM 6032M], GM Dex-IIC [6137M] GM Dex-IIID [GM 6137M], GM ATF WS, GM Dex-IIIE [GM 6137M]/-IIIF [GM 6297M], GM 88863400, GM Dex-IIIG [GM 6417M]/-IIIH [GM N10055], GM 19 40 700/19 40 767/88863401/21005966, GM 88900925/9985010/9986195, HYUNDAI ATF SP-IV/ATF RED-1K/Genuine ATF/JWS 3314, HYUNDAI 00232-19023/040000C90SG/04500-00140/UM040 CH20 Red-1/SP/SP4-M1/SPH-IV, HYUNDAI/KIA SP-II/-III/-IV/-IV-RR, HYUNDAI WS, spec NWS-9638, KIA SP4-M1, KIA ATF RED-1K, KIA WS, spec NWS-9638, KIA Genuine ATF, KIA JWS 3314, KIA 00232-19023/040000C90SG, KIA 04500-00140, KIA SP, KIA UM040 CH20 Red-1, TOYOTA ATF FZ/JWS 3309/08886-81015, TOYOTA Type T, T-II, T-III, T-IV, TOYOTA Type D-II, TOYOTA ATF WS Lifetime, TOYOTA JWS 3324, MB 236.14/A 0019892203/ATF 3403-M115/236.1/236.10/236.11/236.12/236.15/236.2/236.41, MB 236.5, NISSAN Fluid A, NISSAN Matic D/J/K/W, NISSAN N402, NISSAN 999MP-MTJ00P, NISSAN 999MP-MTS00P, NISSAN Matic S, VW LT 71141, VW G 052 162 [Ag4]/052 533, VW G 052 990 A2/055 005 A2/055 025 A2/055 162 A2/055 540 A2/060 162 A2/US 000 162, BMW 81 22 9 400 272/275, BMW 81 22 9 407 858/407 859, BMW 83 22 0 024 249/359, BMW 83 22 0 026 922/142 516/397 114, BMW/MINI 83 22 0 402 413, BMW 83 22 0 403 248, BMW 83 22 0 403 249, BMW 83 22 2 152 426/163 514/220 438/220 440/220 442/289 720, BMW 83 22 2 305 396/305 397/355 599/355 601, BMW 83 22 7 542 290/9 407 765, 9 407 807, MINI ATF JWS 3309, BMW ATF 3+/ATF4/ATF6, BMW ETL-7045/-7045 E/-8072B, BMW LA 2634, BMW LT 71141, BMW M-L12108, FCA ATF+3/ATF+2/ATF+/ASRC, FCA 8 & 9 Speed ATF, FCA AW-1, FCA 68218925AA/68218925AB/68092912AA/68043742AA/Dex-VI/05127382AA/05127382, FCA 68157995AA/68157995AB/68333587AA/SP-IV/SP-III/68171869AA/Type 7176E/Type 9602, FCA ATF+4/68171866AA, ATF M-1375.6/LA 2634/L12108/ETL-7045 E/3403-M115/3100 PL085, ATF 3353/134/K17/N402/M-1375.4, DAIHATSU D3-SP, HONDA ATF DW-1, HONDA ATF Type 3.0/3.1 HONDA 08200-9008/08200-9016-A/08200-9017/08200-9001/08200-9001A, HONDA ATF Z1, ISUZU ATF II/III, ISUZU Genuine ATF/08200-9001/SCS, JAGUAR 02JDE 26444, JAGUAR Fluid 8432, JAGUAR JLM 20238/20292/21044, JAGUAR K17, Jatco 3100 PI085, JAGUAR LT 71141, JAGUAR WSS-M2C922-A1, LAND ROVER ATF N402/AW-1, LR0022460: LV/JWS3309US, LAND ROVER TYK500050/LR023288/LR023289, MAN 339A/D/F, MASERATI Oil No. 231603, MAZDA ATF FZ, ATF N-1, ATF S-1/ATF M-5, 0000-23-ATF -M5/F-1/JWS3317/M3/Type T-IV, JWS 3309, MITSUBISHI DII, MITSUBISHI SP, Ms991156, MITSUBISHI SP-II/-III/-IV, MITSUBISHI ATF-J2, MITSUBISHI ATF-J3, MITSUBISHI DIA Queen ATF-MA1, Mz320775/Dia Queen ATF-PA, 4030401, MITSUBISHI Dia Queen AW, PEUGEOT Z 000169756, PORSCHE JWS 3309/000 043 205 28, PORSCHE LT 71141/000 043 204 63/000 043 304 00/999 917 547 00 (A2)/000 043 205 09, PSA AL4/4HP20/9730AE/B71 2340, RENAULT DP-0, RENAULT Matic D2, RENAULT SATF-D, ROLLS ROYCE Oil No. PL 31493PA, SAAB ATF HP/JWS 3309/93 160 393/93 165 147, SATURN Dex-IIIG/T-IV Fluid/22689186, SSANGYONG DSIH 5M-52/-66, SUBARU ATF HP/ATF-WS, SUBARU K0140V0700/SOA635040, SUZUKI ATF 2326/2384K/3314/3317/5D06, SUZUKI Matic D, SUZUKI Matic J/S, VOLVO 1161521/1161621/1161640/1161540, VOLVO 31 256 774/775, ZF LifeguardFluid 5/6/8/9 (ZF No. S671 090 170), ZF TE-ML 11A/11B

A universal all-season synthetic transmission fluid (ATF) for automatic gearboxes, hydraulic converters, hydraulic power steering systems, car hydraulic clutches and other hydraulic devices, including the ones operating in heavy-duty conditions in trucks and off-road vehicles. It ensures a flawless operation of an automatic gearbox, guarantees minimal wear, a lasting service life of transmissions and fuel economy. It was developed on the basis of the requirements set by GM and Ford groups.

Volume:

1L	MN8207-1	20L	MN8207-20
4L	MN8207-4	60L	MN8207-60
7L	MN8207-7	208L	MN8207-DR
10L	MN8207-10	1000L	MN8207-IBC



Product Characteristics:

Test	Method	Unit	Result
Color			RED
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	CSt	28.29
Viscosity at 100 °C	D 445	CSt	5.94
Viscosity index	D 2270		162
Flash point COC	D 92	°C	214
Pour point	D 97	°C	-52
Brookfield dynamic viscosity at -40 °C	D 2983	°C	9960

www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®