

Product Code:

8209

ATF SP-III

Automatic Transmission Fluid

Meets the requirements:

JASO M315 Type 1A, HYUNDAI ATF RED -1K, HYUNDAI JWS 3314, HYUNDAI 00232-19023/04500-00140/UM040 CH20 Red-1, HYUNDAI SP, HYUNDAI SP-II/-III, KIA ATF RED-1K, KIA JWS 3314, KIA 00232-19023/04500-00140, KIA UM040 CH20 Red-1, KIA SP, KIA SP-II/-III, MITSUBISHI ATF-J2, MITSUBISHI Dia Queen AW, MITSUBISHI DII, MITSUBISHI DIII, MITSUBISHI SP, MS991156, MITSUBISHI SP-II, MITSUBISHI SP-III

A special synthetic transmission fluid (ATF) for automatic gearboxes of MITSUBISHI, HYUNDAI, KIA vehicles. It ensures a flawless operation of an automatic gearbox, guarantees minimal wear, a lasting service life of transmissions and fuel economy. It is designed on the basis of the requirements set by Korean car manufacturers.

Product Characteristics:

Test	Method	Unit	Result
Color	visual		RED
Density at 15 °C	D 1298	kg/m ³	850
Viscosity at 40 °C	D 445	CSt	34.78
Viscosity at 100 °C	D 445	CSt	6.94
Viscosity index	D 2270		165
Flash point COC	D 92	°C	216
Pour point	D 97	°C	-48
Brookfield dynamic viscosity at -40 °C	D 2983	cP(mPas)	18 200
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-

Volume:

1L_{met} MN8209-1 ME

1L	MN8209-1	60L	MN8209-60
4L	MN8209-4	208L	MN8209-DR
20L	MN8209-20	1000L	MN8209-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®