

Product Code:

8211

ATF AG-52

Automatic Transmission Fluid

Meets the requirements:

ACURA ATF-Z1, AISIN WARNER JWS 3309 (T-IV)/3324 (WS), ALLISON TES-389B, ALLISON C-3 & C-4, American Motors ATF +3 (MS7176-E)/ATF RED 1, RED 1K, AUDI 5 HP LT71141 (ZF 5 HP 18FL/19FL/24A), AUDI G 052 025-A2/053 025-A2, AUDI G 052 162-A1/A2 (ZF Lifeguardfluid 5)/055 025 A2 (JWS 3309)/052 055, AUDI G 052 990, BMW JWS 3309 (T-IV), BMW LA2634, BMW 7045/ETL-8072B, BMW LT71141 (ZF 5 HP 18FL/19FL/24A), BMW ZF 5HP18FL, 5HP24, 5HP30, MINI COOPER T-IV, MINI 83 22 0 402 4132, BOSCH TE-ML 09, CAT TO-2, CHRYSLER ATF+, +2, +3 (MS 7176E)/MOPAR AS 68 RC (T-IV), JWS 3309, DAEWOO LT 71141, DAIHATSU AMMIX ATF D-II/D-III SP, DODGE 05127382AA, DODGE MOPAR AS 68 RC (T-IV), JWS 3309, JEEP 05127382AA, ESSO LT 71141, FIAT T-IV type, JWS 3309, FORD MERCON/FNR5/WSS M2C 138CJ, 166H, FORD WSS M2C 922A1, 924A (XT-8-QAW) JWS 3309/XT-2-QDX (M), FORD XT-2-QSM (Syn)/ESP-M2C166H, XL-12, Fuso ATF-II/ATF-SPIII/ATF-A4, GM 9986195 (Aisin AW, JWS 3309)/TASA, GM DEXRON®-II/-IID/-IIE/-IIIG/-IIIH, GM 1940700/1940767/21005966/22717466/88900925/93160393/88863400/Aw1, GM 88863401, HINO Blue ribbon ATF, HONDA ATF-Z1 (except in CVTs)/DW-1, HYUNDAI SP-III/Dex-II/ SP-II/JWS 3314/040000C90SG, IDEMITSU K17 3100 PL085, ISUZU BESCO ATF-II/-III, JAGUAR ATF 3403 M115/ATF LT71141, ZF 5HP24, JAGUAR ATF 3403 JLM20238/JLM 20292, JASO M315-2015 1A/2A, JEEP ATF+3, LEXUS JWS 3309, KIA ATF SP-II, SP-III, MAZDA Mazda ATF D-II/M-III/M-V, MAZDA Mazda ATF F-1/S-1/N-1, MAZDA ATF 3317, MB ZF 4HP20, MITSUBISHI Diaqueen SK/SP-II/SP-III/AW/J2, Cherokee NAG 1 (Chrysler, Jeep), NISSAN Matic Fluid C/D/J/K, OPEL 19 40 700/19 40 707/19 40 767/22 17466, OPEL 21005966 Transaxle/88900925/9986195, PEUGEOT Z 000169756, PEUGEOT (PSA) AL4 Automatic gearbox oil (#9730.AE), PORSCHE ATF 3403-M115, PORSCHE ZF 5HP19FL, ZF 5HP20, Lt71141/T-IV (JWS 3309)/000 043 205 09, PORSCHE 999 917 547 00 (A2)/000 043 205 28/Z 000169756, RENAULT DPO/AL4, RENAULT Matic D2, Samsung SATF-D, SAAB T-IV (JWS 3309) and many more



A special all-season synthetic transmission fluid (ATF) for modern 4-5-speed automatic transmission gearboxes of the ZF Group.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	35.01
Viscosity at 100 °C	D 445	cSt	7.16
Viscosity index	D 2270		135
Flash point COC	D 92	°C	214
Pour point	D 97	°C	-50
Brookfield dynamic viscosity at -40 °C	D 2983	cP(mPas)	17 800

Volume:

1L	MN8211-1	20L	MN8211-20
4L	MN8211-4	60L	MN8211-60
10L	MN8211-10	208L	MN8211-DR

www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®