

Product Code:

8213

ATF AG-60

SEE MORE
ONLINE



Automatic Transmission Fluid

Meets the requirements:

JASO M315, Class 1-A-LV, AISIN WARNER AW-2, ALLISON C2/C3/C4, ATF N402, AISIN WARNER JWS 3309 ATF, ATF-OT4, AISIN WARNERJWS 3324 ATF, ATF-OWS, ATF M-1375.6, ATF 134, ATF 3353, ATF 3100 P1085, ATF 3403-M115, ATF D971, ATF ETL-7045 E, ATF K17, ATF L12108, ATF LA 2634. ATF M-1375.4, BMW ATF4, BENTLEY PY112995PA, BMW ATF 3+, BMW ATF6, BMW ETL-7045/-7045 E, BMW ETL-8072B/LA 2634/LT 71141/M-L12108, BMW 81 22 9 400 272/9 400 275, BMW 81 22 9 407 858/81 22 9 407 859/83 22 0 024 249/83 22 0 024 359, BMW 83 22 0 026 922/0 142 516/0 397 114/0 403 248/0 403 249/2 152 426, BMW/MINI 83 22 0 402 413, HYUNDAI SP-III, BMW 83 22 2 163 514/2 220 438, BMW 83 22 2 220 440/2 220 442/2 289 720/2 305 396/2 305 397/2 355 599, BMW 83 22 2 355 601/83 22 7 542 290/83 22 9 407 765/83 22 9 407 807, BOSCH TE-ML 09, CITROEN Z 000169756, DAIHATSU D3-SP, FCA ASRC/ATF+/ATF+2, FCA ATF+3/ATF+4, FCA 8 & 9 Speed ATF, 68218925AA/68218925AB, FCA SP-III, FCA AW-1 68092912AA, FCA DEX-VI 68043742AA, FCA MB 236.10/12 05127382AA, FCA 05127382/68157995AA/68157995AB/68333587AA/SP-4 68171866AA, GM WS, FCA SP-IV, 68171866AA/68171869AA, FCA Type 7176E/9602, GM AW-1 19256039, FORD ESP-M2C138-CJ/ESP-M2C166-H/XT-10-QLV [LV]/XT-12-ULV [ULV], HYUNDAI SP, FORD XT-2-QDX [M]/XT-2-QDM [Syn]/XT-5-QM [V]/XT-5-QSM [V Syn]/XT-6-QSP [SP], FORD XT-8-QAW [Premium]/XT-9-QMM5 [FRN5]/Spec WSS-M2C922-A1, ISUZU ATF III, GM ATF Z1, Saturn 22717466, GM Dex [GM 6032M], GM Dex HP [GMW 16974], GM DEX ULV, 19352619/Dex-B [GM 6032M]/DEX-IIC [6137M]/Dex-IID [GM 6137M], GM Dex-IIIE [GM 6137M]/Dex-IIIF [GM 6297M]/Dex-IIIG [GM 6417M], GM 19 40 700, GM Dex-IIIH [GM N10055]/Dex-VI [GMW 16444], GM 19 40 767/21005966, GM 88900925/9985010/9986195, GM Saturn T-IV Fluid, GM Saturn 22689186, GLOBAL Type A Suffix A, GM 88863400/88863401, HONDA ATF DW-1 08200-9008, HONDA ATF Type 3.0 08200-9016-A/Type 3.1 08200-9017-A, HYUNDAI ATF RED-1K, HONDA ATF Z1, 08200-9001/ATF Z1, 08200-9001A/ATF DW-1 08200-9008, KIA SP-IV, ACURA ATF Type 3.0 08200-9016-A/ATF Type 3.1 08200-9017/ATF Z1, 08200-9001, ACURA ATF Z1, 08200-9001A, HYUNDAI ATF SP-IV/Genuine ATF/00232-19023, HYUNDAI 040000C90SG/04500-00140/UM040 CH20 Red-1/SP4-M1/SPH-IV/SP-II, HYUNDAI SP-IV/SP-IV-RR/WS, spec NWS-9638, KIA ATF RED-1K/ATF SP-IV, KIA Genuine ATF/JWS 3314/00232-19023/040000C90SG/04500-00140/SP/SP-II, KIA UM040 CH20 Red-1/SP4-M1/SPH-IV/SP-III/WS, spec NWS-9638, ISUZU ATF II, ISUZU Genuine ATF/08200-9001/SCS, JAGUAR 02JDE 26444/Fluid 8432/JML 20238, JAGUAR JLM 20292/LM 21044/K17, JATCO 3100 PL085/LT 71141/WSS-M2C922-A1 and many more

A special all-season synthetic transmission fluid (ATF) for modern 8-speed automatic gearboxes of all types and 6-speed automatic gearboxes of the ZF Group.

Product Characteristics:

Test	Method	Unit	Result
Color	visual		GREEN
Density at 15 °C	D 1298	kg/l	830
Viscosity at 40 °C	D 445	cSt	26.53
Viscosity at 100 °C	D 445	cSt	5.79
Viscosity index	D 2270		171
Flash point COC	D 92	°C	218
Pour point	D 97	°C	-50
Brookfield dynamic viscosity at -40 °C	D 2983	cP(mPas)	10 550



Volume:

1L	MN8213-1	20L	MN8213-20
4L	MN8213-4	60L	MN8213-60
10L	MN8213-10	208L	MN8213-DR
		1000L	MN8213-IBC

www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®