

Product Code:

8215

ATF

Automatic Transmission Fluid

Meets the requirements:

MB 236.15, MB 722.9, MB NAG2FE+, MB 0019897903,
MB 001989780310, MB 001989780311, SSANGYONG

A special low-viscosity synthetic transmission fluid (ATF) for automatic gearboxes of vehicles. It ensures a flawless operation of an automatic gearbox, guarantees minimal wear, a lasting service life of transmissions and fuel economy.

Product Characteristics:

Test	Method	Unit	Result
Color	visual		BLUE
Density at 15 °C	D 1298	kg/l	830
Viscosity at 40 °C	D 445	cSt	16.07
Viscosity at 100 °C	D 445	cSt	4.14
Viscosity index	D 2270		171
Flash point COC	D 92	°C	214
Pour point	D 97	°C	-48
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Brookfield dynamic viscosity at -40 °C	D 2983	cP(mPas)	9 500

Volume:

1L	MN8215-1	60L	MN8215-60
20L	MN8215-20	208L	MN8215-DR
		1000L	MN8215-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®