

Product Code:

8216

ATF CVT

Continuously Variable Transmission Fluid

Meets the requirements:

VOLKSWAGEN G 052 180, BMW 83 22 0 429 154, BMW CVT EZL 799A, CHRYSLER CVT FLUID NS-2, DAIHATSU AMIX CVT FLUID DC, MB 236.20, FORD WSS M2C928-A, FORD WSS M2C933-A, FORD CVT FLUID 23, FORD CVT FLUID 30, FORD Mercon CGM DEX-CVT, LEXUS, INFINITI, HONDA HMMF (08260-99904), HONDA HCF-2, MOPAR CVTF +4, JEEP CVT FLUID NS-2, MAZDA CVT FLUID JWS 3320, MINI CVT EZL 799A, MINI 83 22 0 429 154, MITSUBISHI DIAQUEEN CVT FLUID J1/CVT FLUID J4, NISSAN CVT FLUID NS-1/NS-2 (KLE52-00004), SUBARU i-CVT FLUID, SUBARU CVT OIL FOR LINEARTRONIC (K0425Y0710), SUBARU i-CVT FLUID FG, SUZUKI SCVT FLUID, SUZUKI CVT OIL, SUZUKI CVT FLUID GREEN 1/2, TOYOTA CVT FLUID TC/CVT FLUID FE

A special synthetic gear oil for CVT (Continuously Variable Transmission) – variable-speed gears. It was specially developed for use in continuously variable transmissions with a rigid articulated chain or a steel pull chain. It ensures a flawless operation of an automatic gearbox, guarantees minimal wear, a lasting service life of a transmission and fuel economy.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	CSt	35.95
Viscosity at 100 °C	D 445	CSt	6.87
Viscosity index	D 2270		163
Flash point COC	D 92	°C	210
Pour point	D 97	°C	-45
Brookfield dynamic viscosity at -40 °C	D 2983	cP(mPas)	19 000
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-



Volume:

1L	MN8216-1		
4L	MN8216-4	60L	MN8216-60
10L	MN8216-10	208L	MN8216-DR
20L	MN8216-20	1000L	MN8216-IBC

www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®