

Product Code:

8218

ATF MULTIVEHICLE

Automatic Transmission Fluid

Meets the requirements:

SAE JWS 3309, VW G 052 025-A2/162-A1/990-A1/990-A2, VW G 055 025-A1/-A2, BMW 83 22 0 403 248/2 163 514/9 407 765 (LA 2634), BMW 83 22 9 407 807, BMW 7045E (3 Series), BMW ETL-8072B (5 Series), BMW LT71141 (ZF 5 Speed), CHRYSLER ATF+3/ATF+4, FORD Mercon V/SP/LV, FORD Mercon ATF Type F, FORD XT-8-QMM5 [FRN5], GM Dexron II/II D/E/F/G/H, DAIHATSU ALUMIX ATF MULTI, HONDA ATF-Z1 (not for CVT), HONDA ATF DW-1, HYUNDAI/KIA ATF SP-II/-III, IDEMITSU K17-Jaguar X Type 2001-2005, MB 236.1, INFINITI Matic D/J/K, JATCO ATF 3100 PI085, MAN 339 F/V1/V2/Z1/Z2, MAZDA ATF M-III/-V, MB 236.2/236.3/236.5/236.6/236.7/236.9/236.10/236.11, MITSUBISHI DIAMOND SP-II/-III, MOPAR AS68RC, NISSAN Matic D/J/K, PORSCHE JWS 3309, SUBARU ATF-5/-HP, SUZUKI 3314/3317/2384K, SUZUKI ATF OIL, SUZUKI ATF OIL SPECIAL, TOYOTA/LEXUS ATF Type T/T-II/-III/-IV, VOITH 55.6335.XX (G607), VOLVO 97340/97341, ZF TE-ML 03D/04D/11B/14A, ZF TE-ML 14B/16L/17, Others TEXACO N402 (JATCO FWD)/ETL 7045E/ETL 8072B/MOBIL ATF LT 71141

A universal all-season high-viscosity synthetic transmission fluid (ATF) for automatic gearboxes. It was specially developed for all modern automatic gearboxes (manual or sequential modes, electronic control, etc.) equipped with and without a hydraulic converter lock-up. It is also compatible with old-generation automatic gearboxes, hydraulic power steering systems, ship reversing gears, hydrostatic transmissions, hydraulic/mechanical systems in which the use of fluids that correspond to Dexron (except Dexron VI) or Mercon standards is prescribed.

It ensures a flawless operation of an automatic gearbox, guarantees minimal wear, a lasting service life of transmissions and fuel economy. It was developed on the basis of the requirements set by the company AISIN WARNER.

Product Characteristics:

Test	Method	Unit	Result
Color	visual		RED
Brookfiel dynamic viscosity at -40 °C	D 2983	[cP](mPas)	17 500
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	CSt	37.02
Viscosity at 100 °C	D 445	CSt	7.02
Viscosity index	D 2270		154
Flash point	D 92	°C	216
Pour point	D 97	°C	-50
Ignition temperature			350
Mechanical impurities	D 2273	%	-

Volume:

1L	MN8218-1		
10L	MN8218-10	4L	MN8218-4
20L	MN8218-20	60L	MN8218-60
208L	MN8218-DR	1000L	MN8218-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®