

Product Code:

8219

ATF SP-IV

Automatic Transmission Fluid

Meets the requirements:

JASO M315, Class 1-A-LV, ACURA DW-1, ACURA/HONDA ATF Type 3.0/3.1, ACURA ATF Z1, 08200-9001/-9001A, BENTLEY PY112995PA, HONDA DW-1, BMW 83 22 0 142 516 (1375.4), BMW 83 22 0 397 114/2 152 426, KIA SP, BMW 83 22 2 289 720/163 514/305 397, CHRYSLER 05127382AA, KIA SP-II, CHRYSLER 68043742AA/68157995AA, DODGE 05127382AA, HYUNDAI SP, DODGE 68043742AA/68157995AA, FORD XT-10-QLVC/-6-QSP, KIA SP4-M1, FORD XT-6-DSP, HONDA ATF Z1, 08200-9001/A, HYUNDAI NWS-9638 T-5, HYUNDAI SP4-M1/SP-II/SP-III/SP-IV/SPH-IV/SP-IV-RR/ATF RED -1K, KIA SP-III, HYUNDAI Genuine ATF/JWS 3314/00232-19023/040000C90SG, KIA SP-IV, HYUNDAI 04500-00140/UM040 CH20 Red-1, INFINITI Matic S/W, KIA SPH-IV, JAGUAR Fluid 8432, JEEP 05127382AA/68043742AA/68157995AA, MAZDA FZ, KIA NWS-9638 T-5, KIA SP-IV-RR, KIA ATF RED-1K/Genuine ATF/JWS 3314, KIA 00232-19023/040000C90SG/04500-00140/UM040 CH20 Red-1, LAND ROVER TYK500050/LR0022460, LEXUS Scion FZ/Type WS, MB 236.12, LEXUS JWS 3324, LINCOLN XT-10-QLVC, LINCOLN XT-6-QSP/-DSP [SP], MASERATI 231603, MAZDA FW 6A EL/6AX EL, MB 236.14/236.15/236.41, MERCURY XT-10-QLVC/-6-QSP, MINI 83 22 0 142 516/83 22 0 397 114, MINI 83 22 2 152 426/83 22 2 289 720/83 22 2 163 514/83 22 2 305 397, MITSUBISHI ATF-J3/Dia Queen ATF-PA, NISSAN Matic S/W, MITSUBISHI DII, OPEL GM SATURN GMC AW1-VI/88863400/88863401, TOYOTA Scion FZ, PORSCHE 000 043 304 00, SAAB 93 165 147 AW-1, MITSUBISHI ATF-J2, TOYOTA Type WS (JWS 3324), ZF Lifeguardfluid 6/Lifeguardfluid 8, MERCURY XT-6-DSP, MITSUBISHI Dia Queen ATF-MA1 MZ320775, MITSUBISHI Dia Queen AW, MITSUBISHI DIII, MITSUBISHI SP, MS991156

Special low viscosity synthetic gear oil (ATF) with a special additive package for Hyundai 6-speed automatic transmissions. Designed based on the requirements of Korean automakers.

Product Characteristics:

Test	Method	Unit	Result
Color	visual		RED
Brookfiel dynamic viscosity at -40 °C	D 2983	[cP](mPas)	10 500
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	CSt	28.26
Viscosity at 100 °C	D 445	CSt	5.82
Viscosity index	D 2270		156
Flash point	D 92	°C	216
Pour point	D 97	°C	-50
Ignition temperature			350
Mechanical impurities	D 2273	%	-

Volume:

1L	MN8219-1	4L	MN8219-4
20L	MN8219-20	60L	MN8219-60
208L	MN8219-DR	1000L	MN8219-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®