

I40 Premium Quality Engine Oil



Corresponds with requirements / specifications / products:

SAE 15W-40
API SN/CH-4
ACEA A3/B4
VOLKSWAGEN 505.00
VOLKSWAGEN 502.00
VOLKSWAGEN 501.01
VOLKSWAGEN 500.00
MB 229.3
MB 229.1
PSA B71 2294
RENAULT RN0700
RENAULT RN0710

Volume:

1 L (PM0140-1)	4 L (PM0140-4)
5 L (PM0140-5)	20 L (PM0140-20)
60 L (PM0140-60)	208 L (PM0140-DR)

Highly refined economy-class mineral engine oil for highly accelerated petrol and diesel engines with or without a turbocharger, with a very high mileage used in varying operating conditions.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 445	kg/l	890
Viscosity at 40 °C	D 445	cSt	109.0
Viscosity at 100 °C	D 445	cSt	14.38
Dynamic viscosity at -20 °C	D 5293	cP(mPas)	5 837
Viscosity index	D 2270		135
Flash point COC	D 92	°C	226
Pour point	D 97		-38
Ignition temperature		°C	350
Mechanical impurities	D 2273		-

We reserve the right to alter the general characteristics of our products in order to let our consumers benefit from the latest technical development.