

## 260 Superior Quality Engine Oil



### Corresponds with requirements / specifications / products:

SAE 10W-40  
API SN/CH-4  
ACEA A3/B4  
JASO MA2  
VOLKSWAGEN 505 00  
VOLKSWAGEN 502 00  
VOLKSWAGEN 501 01  
VOLKSWAGEN 500 00  
MB 229.3  
MB 229.1  
PSA B71 2296  
RENAULT RN0710  
RENAULT RN0700

### Volume:

|                  |                     |
|------------------|---------------------|
| 1 L (PM0260-1)   | 4 L (PM0260-4)      |
| 5 L (PM0260-5)   | 7 L (PM0260-7)      |
| 20 L (PM0260-20) | 208 L (PM0260-DR)   |
| 60 L (PM0260-60) | 1000 L (PM0260-IBC) |

Universal ester-containing HC-synthese engine oil for modern gasoline and diesel engines with and without a turbocharger, both multi-valve and direct injection, including "old" brands and high mileage vehicles. Designed according to the requirements of European manufacturers.

### Product Characteristics:

| Characteristics                             | Method | Unit              | Value |
|---------------------------------------------|--------|-------------------|-------|
| Density at 15 °C                            | D 1298 | kg/m <sup>3</sup> | 870   |
| Viscosity at 40 °C                          | D 445  | cSt               | 93.57 |
| Viscosity at 100 °C                         | D 445  | cSt               | 13.98 |
| Viscosity index                             | D 2270 |                   | 152   |
| Flash point COC                             | D 92   | °C                | 226   |
| Pour point                                  | D 97   | °C                | -39   |
| TBN                                         | D 2896 | mgKOH/g           | 10.79 |
| Dynamic viscosity [cP], at -25 °C, max      | D 5293 | °C                | 6069  |
| High shear rate viscosity cP at 150 °C, min | D 4741 | °C                | 3.70  |

We reserve the right to alter the general characteristics of our products in order to let our consumers benefit from the latest technical development.