



Corresponds with requirements / specifications / products:

SAE 5W-20
API SP (RC)
ILSAC GF-6A
GM dexos1 Gen2
HONDA HTO-06
GM 6094M
CHRYSLER MS-6395
CHRYSLER MS-13340
JAGUAR STJLR.51.5122
LAND ROVER STJLR.51.5122
FIAT 9.55535-CR1
FORD WSS-M2C930-A
FORD WSS-M2C930-B
FORD WSS-M2C948-A
FORD WSS-M2C948-B

Volume:

1 L (PM0325-1) 4 L (PM0325-4)
20 L (PM0325-20) 208 L (PM0325-DR)

Innovative energy-saving premium bi-synthetic engine oil (PAO + esters) for modern gasoline engines. Designed to meet the requirements of American, Japanese and Korean automakers.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 445	kg/l	850
Viscosity at 40 °C	D 445	cSt	40.67
Viscosity at 100 °C	D 445	cSt	7.67
Dynamic viscosity at -30 °C	D 5293	cP(mPas)	5507
Viscosity index	D 2270		161
Flash point COC	D 92	°C	224
Pour point	D 97		-45
High shear rate, viscosity at 150 °C	D 4741	cP	2.94
TBN	D 2896	mgKOH/g	8.03
Ignition temperature		°C	350
Mechanical impurities	D 2273		-

We reserve the right to alter the general characteristics of our products in order to let our consumers benefit from the latest technical development.