

328 Fully Synthetic Engine Oil



Corresponds with requirements / specifications / products:

SAE 0W-20
ACEA C5
API SP (RC)
MB 229.71
BMW LL-17FE+
VOLVO VCC RBS0-2AE (Service Fill)
GM dexos1 Gen2
OPEL OV0401547
HONDA HTO-06
GM 6094M
CHRYSLER MS-6395
CHRYSLER MS-13340
JAGUAR STJLR.51.5122
LAND ROVER STJLR.51.5122
FORD WSS-M2C947-A
FORD WSS-M2C947-B1

Volume:

1 L (PM0328-1) 4 L (PM0328-4)
5 L (PM0328-5) 20 L (PM0328-20)
60 L (PM0328-60) 208 L (PM0328-DR)
1000 L (PM0328-IBC)

Innovative energy-saving, low-viscosity bi-synthetic (PAO + esters) premium engine oil for the latest models of turbocharged gasoline engines (multipoint or direct injection) with diesel particulate filters.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 445	kg/l	830
Viscosity at 40 °C	D 445	cSt	39.86
Viscosity at 100 °C	D 445	cSt	7.69
Dynamic viscosity at -35 °C	D 5293	cP(mPas)	5175
Viscosity index	D 2270		166
Flash point COC	D 92	°C	224
Pour point	D 97		-45
TBN	D 2896	mgKOH/g	8.08
Ignition temperature		°C	350
Mechanical impurities	D 2273		-

We reserve the right to alter the general characteristics of our products in order to let our consumers benefit from the latest technical development.